



भारतीय सूचना प्रौद्योगिकी संस्थान गुवाहाटी  
Indian Institute of Information Technology Guwahati

Dept./Section/Centre: Works Section

Ref: NIQ No. IIITG/Works/42/2023/129

Date:26.06.2023

To,

**Interested Vendors/Contractors**

**Sub:** Notice Inviting Quotation (NIQ) for Partition Wall in Store Room of Boys Hostel & Partition wall in room nos 224, 231, 314, 307 & 428 of Admin Building at IIIT Guwahati.

**Dear Sir,**

The undersigned invites sealed quotations from the local vendors/contractors for onward submission along with requisite documents for the work of "Partition Wall in Store Room of Boys Hostel & Partition wall in room nos 224, 231, 314, 307 & 428 of Admin Building at IIIT Guwahati Campus" in the form of BOQ (Bill of Quantities).

Sl No.	Particulars	Details of Works
1	Name of Works	Partition Wall in Store Room of Boys Hostel & Partition wall in room nos 224, 231, 314, 307 & 428 of Admin Building at IIIT Guwahati Campus.
2	Completion period	25 days
3	Last Date & Time of Submission of BOQ	04.07.2023 up to 2.30 pm
4	Date & Time of opening	04.07.2023 at 3.30 pm
5	Scope of work	As detailed in the BOQ
6	SD money	3% will be deducted which will be released after 6 months from the date of completion.

You are requested to submit your rates in the given BOQ format (with your working rates in the rate's column) with the proof of following documents:-

1. The bidder must have a valid Govt./Semi Govt. contracting registration with working experience of successfully completed similar works during the last seven years ending previous day of last date of submission of tender as under:  
**Three similar completed works costing each not less than ₹1.02 Lakh, or  
Two similar completed works, each of value not less than ₹ 1.53 Lakh, or  
One similar completed work of value not less than ₹2.04 lakh.**
2. The Bidder should have GSTN, PAN and own Bank Account.
3. Other terms & Condition will be as per IIITG rule.
4. The rates Quoted by the bidder shall be inclusive of GST, other statutory taxes/cess/royalties as may be applicable.

Sd/-  
Associate Dean ( Admin)

## BOQ Format for NIQ No: IITG/Works/42/2023/129

Sl. No.	Description Of Item	Unit	Qty	Rate	Amount(₹)
1	<p>Providing and fixing partition upto ceiling height consisting of G.I. frame and required board, including providing and fixing of frame work made of special section power pressed/ roll form G.I. sheet with zinc coating of 120 gms/sqm(both side inclusive), consisting of floor and ceiling channel 50mm wide having equal flanges of 32 mm and 0.50 mm thick, fixed to the floor and ceiling at the spacing of 610 mm centre to centre with dash fastener of 12.5 mm dia meter 50 mm length or suitable anchor fastener or metal screws with nylon plugs and the studs 48 mm wide having one flange of 34 mm and other flange 36 mm and 0.50 mm thick fixed vertically within flanges of floor and ceiling channel and placed at a spacing of 610 mm centre to centre by 6 mm dia bolts and nuts, including fixing of studs along both ends of partition fixed flush to wall with suitable anchor fastener or metal screws with nylon plugs at spacing of 450 mm centre to centre, and fixing of boards to both side of frame work by 25 mm long dry wall screws on studs, floor and ceiling channels at the spacing of 300 mm centre to centre. The boards are to be fixed to the frame work with joints staggered to avoid through cracks, M.S. fixing channel of 99 mm width (0.9 mm thick having two flanges of 9.5 mm each) to be provided at the horizontal joints of two boards, fixed to the studs using metal to metal flat head screws, including jointing and finishing to a flush finish with recommended jointing compound, jointing tape, angle beads at corners (25 mm x 25 mm x 0.5 mm), joint finisher and two coats of primer suitable for board as per manufacture's specification and direction of engineer in charge all complete. 9.105.1 75 mm overall thickness partition with 12.5 mm thick double skin fire rated Glass Reinforced Gypsum (GRG) plaster board conforming to IS: 2095: part 3 (Board with BIS certification marks)</p>				
	75 mm overall thickness partition with 12.5 mm thick double skin fire rated Glass Reinforced Gypsum (GRG) plaster board conforming to IS: 2095: part 3 (Board with BIS certification marks)	<b>Sqm</b>	<b>84.00</b>		

Sl. No.	Description Of Item	Unit	Qty	Rate	Amount(₹)
2	Providing and applying plaster of paris putty of 2 mm thickness over plastered surface to prepare the surface even and smooth complete.	Sqm	168.00		
3	Distempering with 1st quality acrylic distemper (ready mixed) having VOC content less than 50 gms/litre, of approved manufacturer, of required shade and colour complete, as per manufacturer's specification.				
	Two or more coats on new work	Sqm	270.00		
4	Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/ appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / paneling, C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing, paneling and dash fasteners to be paid for separately) :				
	For shutters of doors, windows & ventilators including providing and fixing hinges/ pivots and making provision for fixing of fittings wherever required including the cost of EPDM rubber / neoprene gasket required (Fittings shall be paid for separately)				
	Powder coated aluminium (minimum thickness of powder coating 50 micron) kg	KG	29.4		
5	Providing and fixing aluminium tower bolts, ISI marked, anodised (anodic coating not less than grade AC 10 as per IS : 1868 ) transparent or dyed to required colour or shade, with necessary screws etc. complete :				
	300x10mm	Each	2.00		

Sl. No.	Description Of Item	Unit	Qty	Rate	Amount(₹)
6	Providing and fixing bright finished brass 100 mm mortice latch and lock, ISI marked, with six levers and a pair of anodised (anodic coating not less than grade AC 10 as per IS : 1868) aluminium lever handles of approved quality with necessary screws etc. complete.	Each	2.00		
7	Providing and fixing aluminium hanging floor door stopper, ISI marked, anodised (anodic coating not less than grade AC 10 as per IS : 1868) transparent or dyed to required colour and shade, with necessary screws etc. complete.				
	Single rubber stopper each	Each	2.00		
8	Providing and fixing skirting with Pre-laminated (one side decorative and other side balancing lamination) flat pressed 3 layer or graded particle board (medium density) Grade I, Type II, IS :12823 marked, with necessary fixing arrangements and screws, including drilling necessary holes for rawl plugs etc. and priming coat on unexposed surface complete :				
	18 mm thick sqm	Sqm	6.00		
<b>Total(₹)</b>					