



भारतीय सूचना प्रौद्योगिकी संस्थान गुवाहाटी
Indian Institute of Information Technology Guwahati

Dept./Section/Centre: Works Section

Ref: NIQ No. IIITG/Works/40/2023/126

Date:21.06.2023

To,

Interested Vendors/Contractors

Sub: Notice Inviting Quotation (NIQ) for Repairing of water leakage in RCC water Tank in Tower 1 Faculty Building at IIIT Guwahati campus.

Dear Sir,

The undersigned invites sealed quotations from the local vendors/contractors for onward submission along with requisite documents for the work "Repairing of water leakage in RCC water Tank in Tower 1 Faculty Building at IIIT Guwahati campus". in the form of BOQ (Bill of Quantities).

Sl No.	Particulars	Details of Works
1	Name of Works	Repairing of water leakage in RCC water Tank in Tower 1 Faculty Building at IIIT Guwahati campus.
2	Completion period	20 days
3	Last Date & Time of Submission of BOQ	29.06.2023 up to 2.30 pm
4	Date & Time of opening	29.06.2023 at 3.30 pm
5	Scope of work	As detailed in the BOQ
6	SD money	3% will be deducted which will be released after 6 months from the date of completion.

You are requested to submit your rates in the given BOQ format (with your working rates in the rate's column) with the proof of following documents.

TERMS & CONDITIONS:

1. The bidder must have a valid Govt./Semi Govt. contracting registration with working experience of successfully completed similar works, viz. water proofing treatment work in RCC water Tank during the last seven years ending previous day of last date of submission of tender as under:

***Three similar completed works costing each not less than ₹40Thousand, or
Two similar completed works, each of value not less than ₹ 60 Thousand, or
One similar completed work of value not less than ₹80Thousand.***

2. The Bidder should have GSTN, PAN and own Bank Account.

3. Other terms & Condition will be as per IIITG rule.

4. The rates Quoted by the bidder shall be inclusive of GST, other statutory taxes/cess/royalties as may be applicable.

Sd/-

Associate Dean(Admin)

BOQ Format

SL No	Description of works	Unit	Qty.	Rate	Amount (₹)
1	Labour for dismantling & removing debries	nos	70.00		
2	Providing and laying vitrified floor tiles in different sizes (thickness to be specified by the manufacturer) with water absorption less than 0.08% and conforming to IS: 15622, of approved make, in all colours and shades, laid on 20mm thick cement mortar 1:4 (1 cement : 4 coarse sand), jointing with grey cement slurry @ 3.3 kg/ sqm including grouting the joints with white cement and matching pigments etc., complete.				
	Size of Tile 600x600 mm sqm	sqm	11.76		
3	Providing and fixing false ceiling at all height including providing and fixing of frame work made of special sections, power pressed from M.S. sheets and galvanized with zinc coating of 120 gms/sqm (both side inclusive) as per IS : 277 and consisting of angle cleats of size 25 mm wide x 1.6 mm thick with flanges of 27 mm and 37mm, at 1200 mm centre to centre, one flange fixed to the ceiling with dash fastener 12.5 mm dia x 50mm long with 6mm dia bolts, other flange of cleat fixed to the angle hangers of 25x10x0.50 mm of required length with nuts & bolts of required size and other end of angle hanger fixed with intermediate G.I. channels 45x15x0.9 mm running at the spacing of 1200 mm centre to centre, to which the ceiling section 0.5 mm thick bottom wedge of 80 mm with tapered flanges of 26 mm each having lips of 10.5 mm, at 450 mm centre to centre, shall be fixed in a direction perpendicular to G.I. intermediate channel with connecting clips made out of 2.64 mm dia x 230 mm long G.I. wire at every junction, including fixing perimeter channels 0.5 mm thick 27 mm high having flanges of 20 mm and 30 mm long, the perimeter of ceiling fixed to wall/partition with the help of rawl plugs at 450 mm centre, with 25mm long dry wall screws @ 230 mm interval, including fixing of gypsum board to ceiling section and perimeter channel with the help of dry wall screws of size 3.5 x 25 mm at 230 mm c/c, including jointing and finishing to a flush finish of tapered and square edges of the board with recommended jointing compound , jointing tapes , finishing with jointing compound in 3 layers covering upto 150 mm on both sides of joint and two coats of primer suitable for board, all as per manufacturer's specification and also including the cost of making openings for light fittings, grills, diffusers, cutouts made with frame of perimeter channels suitably fixed, all complete as per drawings, specification and direction of the Engineer in Charge but excluding the cost of painting with : 12.5 mm thick tapered edge gypsum plain board conforming to IS: 2095- (Part I) :2011 (Board with BIS certification marks) sqm	sqm	10.29		

SL No	Description of works	Unit	Qty.	Rate	Amount (₹)
4	Distempering with 1st quality acrylic distemper (ready mixed) having VOC content less than 50 gms/litre, of approved manufacturer, of required shade and colour complete, as per manufacturer's specification. Two or more coats on new work	Sqm	22.40		
5	Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/ appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / paneling, C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing, paneling and dash fasteners to be paid for separately) :				
	Polyester powder coated aluminium (minimum thickness of polyester powder coating 50 micron)	kg	100.00		
	For shutters of doors, windows & ventilators including providing and fixing hinges/ pivots and making provision for fixing of fittings wherever required including the cost of EPDM rubber / neoprene gasket required (Fittings shall be paid for separately)				
	Polyester powder coated aluminium (minimum thickness of polyester powder coating 50 micron)	kg	25.20		
6	Providing and fixing 12 mm thick prelaminated particle board flat pressed three layer or graded wood particle board conforming to IS: 12823 Grade I Type II, in panelling fixed in aluminum doors, windows shutters and partition frames with C.P. brass / stainless steel screws etc. complete as per architectural drawings and directions of engineer in-charge.				
	Pre-laminated particle board with decorative lamination on one side and balancing lamination on other side sqm 965.1	sqm	25.00		
Total ₹					
Add GST@____%					
Grand Total					