



भारतीय सूचना प्रौद्योगिकी संस्थान गुवाहाटी  
Indian Institute of Information Technology Guwahati

Dept./Section/Centre: Works

File NIQ No. IIITG/Works/2025-26 /330

Date:12.06.2026

To,

Interested Vendors/Contractors

**Sub:** Notice Inviting Quotation (NIQ: "Repainting of old canteen room and Gypsum partition wall and protection of outdoor panel of Admin building from rain water using MS pipe and GI sheet and Plate from for placement of Aqua guard purifier/cooler in Girls Hostel." at IIIT Guwahati.  
**Dear Sir,**

The undersigned invites sealed quotations from the local vendors/contractors for onward submission along with requisite documents for the work "Repainting of old canteen room and Gypsum partition wall and protection of outdoor panel of Admin building from rain water using MS pipe and GI sheet and Plate from for placement of Aqua guard purifier/cooler in Girls Hostel." at IIIT Guwahati." the form of BOQ (Bill of Quantities) enclosed herewith.

SI No.	Particulars	Details of Works
1	Name of Works	"Repainting of old canteen room and Gypsum partition wall and protection of outdoor panel of Admin building from rain water using MS pipe and GI sheet and Plate from for placement of Aqua guard purifier/cooler in Girls Hostel." at IIIT Guwahati"
2	Completion period	20 days from the date of issue of work order
3	Last Date & Time of Submission of BOQ	19.06.2026 up to 2.30 pm
4	Date & Time of opening	19.06.2026 at 3.30 pm
5	Scope of work	As detailed in the BOQ
6	SD money	2.5% will be deducted which will be released after 3 months from the date of completion.

You are requested to submit your rates in the given BOQ format (with your working rates in the rate's column) with the proof of following documents.

**TERMS & CONDITIONS:**

- 1.The bidder must have a valid Govt./Semi Govt. contracting registration with working experience of Civil work of value not less than Rs. 1,00000/-
- 2.The Bidder should have GSTN, PAN and own Bank Account.
- 3.Other terms & Condition will be as per IIITG rule.
4. The rates Quoted by the bidder shall be inclusive of GST, other statutory taxes/cess/royalties as may be applicable.

  
Dean Administration

**BOQ**

**Name Of Work: Repainting of old canteen room and Gypsum partition wall and protection of outdoor panel of Admin building from rain water using MS pipe and GI sheet and Plate from for placement of Aqua guard purifier/cooler in Girls Hostel.**

Sl.no	Description	Unit	Qty	Rate	Amount
1	Distemping with 1st quality acrylic distember (Ready mix) having VOC content less than 50 grams/ litre of approved brand and manufacture to give an even shade : Old work (one or more coats)	Sqm	278.95		
2	Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and smooth complete.	Sqm	91.41		
3	Applying priming coats with primer of approved brand and manufacture, having low VOC (Volatile Organic Compound ) content. With water thinnable cement primer on wall surface having VOC content less than 50 grams/litre	Sqm	91.41		
4	Labour for Cleaning of kithhen Tilese	Nos	6.00		
5	Providing and fixing partition upto ceiling height consisting of G.I. frame and required board, including providing and fixing of frame work made of special section power pressed/ roll form G.I. sheet with zinc coating of 120 gms/sqm(both side inclusive), consisting of floor and ceiling channel 50mm wide having equal flanges of 32 mm and 0.50 mm thick, fixed to the floor and ceiling at the spacing of 610 mm centre to centre with dash fastener of 12.5 mm dia meter 50 mm length or suitable anchor fastener or metal screws with nylon plugs and the studs 48 mm wide having one flange of 34 mm and other flange 36 mm and 0.50 mm thick fixed vertically within flanges of floor and ceiling channel and placed at a spacing of 610 mm centre to centre by 6 mm dia bolts and nuts, including fixing of studs along both ends of partition fixed flush to wall with suitable anchor fastener or metal screws with nylon plugs at spacing of 450 mm centre to centre, and fixing of boards to both side of frame work by 25 mm long dry wall screws on studs, floor and ceiling channels at the spacing of 300 mm centre to centre. The boards are to be fixed to the frame work with joints staggered to avoid through cracks, M.S. fixing channel of 99 mm width (0.9 mm thick having two flanges of 9.5 mm each) to be provided at the horizontal joints of two boards, fixed to the studs using metal to metal flat head screws, including jointing and finishing to a flush finish with recommended jointing compound, jointing tape, angle beads at corners (25 mm x 25 mm x 0.5 mm), joint finisher and two coats of primer suitable for board as per manufacture's specification and direction of engineer in charge all complete.				
	75 mm overall thickness partition with 12.5 mm thick double skin fire rated Glass Reinforced Gypsum (GRG) plaster board conforming to IS: 2095: part 3 (Board with BIS certification marks)	Sqm	14.31		
6	Structural steel work riveted, bolted or welded in built up sections, trusses and framed work, including cutting, hoisting, fixing in position and applying a priming coat of approved steel primer all complete.	Kg	302.85		

7	Providing and fixing pre-coated galvanised iron profile sheets (size, shape and pitch of corrugation as approved by Engineer-in-charge) 0.50 mm (+ 0.05 %) total coated thickness with zinc coating 120 grams per sqm as per IS: 277, in 240 mpa steel grade, 5-7 microns epoxy primer on both side of the sheet and polyester top coat 15-18 microns. Sheet should have protective guard film of 25 microns minimum to avoid scratches during transportation and should be supplied in single length upto 12 metre or as desired by Engineer in-charge. The sheet shall be fixed using self drilling /self tapping screws of size (5.5x 55 mm) with EPDM seal, complete upto any pitch in horizontal/ vertical or curved surfaces, excluding the cost of purlins, rafters and trusses and including cutting to size and shape wherever required.	Sqm	20.00		
8	Providing and laying in position cement concrete of specified grade excluding the cost of centering and shuttering - All work up to plinth level : 1:2:4 (1 cement : 2 coarse sand (zone-III) derived from natural sources : 4 graded stone aggregate 20 mm nominal size derived from natural sources)	Cum	0.40		
9	Half brick masonry with common burnt clay F.P.S. (non modular) bricks of class designation 7.5 superstructure above plinth level up to floor V level cement mortar 1:4 (1 cement : 4 coarse sand) sqm	Sqm	0.80		
10	Providing and laying Ceramic glazed floor tiles of size 300x300 mm (thickness to be specified by the manufacturer) of 1st quality conforming to IS : 15622 of approved make in colours such as White, Ivory, Grey, Fume Red Brown, laid on 20 mm thick cement mortar 1:4 (1 Cement : 4 Coarse sand), Jointing with grey cement slurry @ 3.3 kg/sqm including pointing the joints with white cement and matching pigment etc., complete.	Sqm	4.00		
11	Providing and fixing 1st quality ceramic glazed wall tiles conforming to IS: 15622 (thickness to be specified by the manufacturer), of approved make, in all colours, shades except burgundy, bottle green, black of any size as approved by Engineer-in-Charge, in skirting, risers of steps and dados, over 12 mm thick bed of cement mortar 1:3 (1 cement : 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per sqm, including pointing in white cement mixed with pigment of matching shade complete.	Sqm	6.00		
12	Providing and fixing Chlorinated Polyvinyl Chloride (CPVC) pipes, having thermal stability for hot & cold water supply including all CPVC plain & brass threaded fittings This includes jointing of pipes & fittings with one step CPVC solvent cement, trenching, refilling & testing of joints complete as per direction of Engineer in Charge.				
	40mm nominal dia Pipes metre	Rmt	8.00		
<b>TOTAL AMOUNT</b>					